

## Surface pipe floats

Multi products special floats are designed considering reduced operativity and maintenance costs. Standard floats are composed of two empty half shells and can be filled with closed-cell polyurethane foam on specific customer request. They are connected to the pipe by galvanized steel strip. Extremely Versatile, They are made of polyethylene rotomoulded modules.



- ✓ Maintenance free
- ✓ Great reliability
- ✓ High value of buoyancy per unit
- ✓ Very quick assembly
- ✓ Possible fast variation of reserve buoyancy
- ✓ Easily stored

## Wide Range

Multi products surface pipeline floats projected for a range from 160 mm to 960 mm external hose diameter. Net buoyancy goes from 47 kg to 1052 kg for each single float.

	DIMENSIONS (mm)			EMPTY (kg)		FILLED (kg)	
	LENGTH	OUTSIDE DIAMETER	INSIDE DIAMETER	WEIGHT	NET BUOYANCY	WEIGHT	NET BUOYANCY
MF 01	550	450	160	16	49	18	47
MF 02	550	450	190	16	49	18	47
MF 03	1200	750	180	42	408	55	395
MF 04	1200	750	200	42	408	55	395
MF 05	1200	750	225	42	408	55	395
MF 06	1200	750	250	42	408	55	395
MF 07	1200	850	265	49	501	65	485
MF 08	1200	850	275	49	501	65	485
MF 09	1200	850	315	49	501	65	485
MF 10	1200	850	350	49	501	65	485
MF 11	1200	850	375	49	501	65	485
MF 12	1200	950	400	57	573	76	554
MF 13	1200	950	450	57	573	76	554
MF 14	1200	1100	450	71	774	105	740
MF 15	1200	1100	500	71	774	105	740
MF 16	1200	1100	550	71	774	105	740
MF 17	1300	1200	600	87	1052	133	1006
MF 18	1300	1200	610	87	1052	133	1006
MF 19	1300	1200	650	87	1052	133	1006
MF 20	870	1660	960	140	910	180	870

